



## **Regular LED Street Light Series**

www.jianyulighting.com

## Model H LED Street Light







## Features & Advantages

- Thickened Die-Cast Aluminum Housing
   Made from pure aluminum die-casting with stainless steel fittings, ensuring durability with anti-corrosion, pressure resistance;
- Convection Cooling Design
   Optimized thermal management, significantly extending LED lifespan;
- Cost-Effective Frameless Design
   Delivering modern simplicity for budget-conscious projects;
- Ultra-High Efficiency LED Chips of more than 200LM/W Features premium SMD LEDs, providing superior brightness;
- Professional Anti-Glare Lens (T2S/T3M)
   Equipped with PC full-cutoff lenses to eliminate light pollution;
- Multiple Control Options
   Including time control, light sensing, IoT connectivity, and 0/1-10V dimming, for intelligent and customizable lighting solutions;
- SKD, OEM, and ODM services available;



| Model      | Power | Size(mm)   | Weight(g) | CRI(RA) | Luminous Efficiency | Viewing Angle | IP Grade |
|------------|-------|------------|-----------|---------|---------------------|---------------|----------|
|            |       |            |           |         |                     |               |          |
| Jh450-50W  | 50W   | 450*78*115 | 409       | ≽80     | 200LM/W             | 70*140°       | Ip65     |
|            |       |            |           |         |                     |               |          |
| JH500-100W | 100W  | 500*78*132 | 471       | ≽80     | 200LM/W             | 70*140°       | Ip65     |
|            |       |            |           |         |                     |               |          |
| JH570-150W | 150W  | 570*78*167 | 586       | ≥80     | 200LM/W             | 70*140°       | Ip65     |
|            |       |            |           |         |                     |               |          |
| JH688-200W | 200W  | 688*78*203 | 762       | ≽80     | 200LM/W             | 70*140°       | Ip65     |