
## **Model RM Regional Module Street Light**





## Features & Advantages

- Scalable & Customizable Design
   Modular design allows seamless extension to fit any project scale, scalable power options from 50W to 600W;
- Flexible Mounting System
   Adjustable rotating handle enables precise angle and light direction control for optimal coverage;
- Thickened Die-Cast Aluminum Housing
   Made from pure aluminum die-casting with stainless steel fittings, ensuring durability with anti-corrosion, pressure resistance;
- Convection Cooling Design
   Optimized thermal management, significantly extending LED lifespan;
- Ultra-High Efficiency LED Chips of more than 200LM/W Features premium SMD LEDs, providing superior brightness;
- Professional Anti-Glare Lens (T2S/T3M)
   Equipped with PC full-cutoff lenses to eliminate light pollution;



Model	Power	Size(mm)	Weight(g)	CRI(RA)	Luminous Efficiency	Viewing Angle	IP Grade
JRM559-150W	150W	559.5*354*99	7010	≥80	200LM/W	70*140°	Ip65
JRM777-300W	300W	777.8*354*99	8260	≥80	200LM/W	70*140°	Ip65
JRM956-450W	450W	956*354*99	11260	≥80	200LM/W	70*140°	Ip65
JRM1134-600W	600W	1134*354*99	13260	≥80	200LM/W	70*140°	Ip65